FULLRIVER
Link our dreams

AC750 Wireless Dual Band Router

FR-WR1046AC-C

Major features

- Supports IEEE802.11ac, compatible with IEEE802.11a/b/g/n
- Dual band for combined wireless speeds up to 750Mbps
- Provide a 10/100M WAN interface and four 10/100M LAN interface

Description

FR-WR1046AC-C comes with the next generation Wi-Fi standard – IEEE802.11ac, support IEEE802.11ac and down compatible with IEEE802.11a/b/g/n. Provide incredibly wireless speed that up to 750Mbps. Device integrated with internet-sharing router and 4-port switch, easy to establish your home or office network. FR-WR1046AC-C is the superior choice for seamless HD streaming, online gaming and other bandwidth-intensive tasks.

FULLRIVER Link our dreams

Application of topology

Wireless 5 Ghz/AC

Wireless 2,4 Ghz

AC750 Wireless Dual Band Router FR-WR1046AC-C

Features

- Supports IEEE802.11ac, compatible with IEEE802.11a/b/g/n
- Dual band for combined wireless speeds up to 750Mbps
- Provide a 10/100M WAN interface and four 10/100M LAN interface
- Supports WDS Wireless Bridge
- Supports 64/128bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
- Built-in firewall, Filtering on IP address, MAC address, Domain name, Applications, etc
- Quick installation guide ,easy configure your settings
- Firmware upgradeable on line

Hardware Specification

Model Name		FR-WR1046AC-C
Chipset		RTL8881AN+RTL8192ER
CPU Frequency		520MHz
RAM capacity		64MByte(DDR2)
ROM capacity		2MByte(SPI flash)
Standards and Protocols	Wireless	5GHz: IEEE 802.11ac,IEEE 802.11n,IEEE 802.11a 2.4GHz: IEEE 802.11n,IEEE 802.11g,IEEE 802.11b
	Wired	IEEE802.3i,IEEE802.3u
Operating Frequency		2.4GHz & 5GHz
Signal Rate		2.4GHz: Up to 300Mbps 5GHz: Up to 450Mbps
Modulation		IEEE 802.11b:CCK，QPSK，BPSK IEEE11g/a:OFDM IEEE11n:QPSK，BPSK，16-QAM，64-QAM IEEE11ac:BPSK，QPSK，16QAM，64QAM，256QAM
Transmit Power		2.4GHz:≦18dBm 5GHz:≦18dBm
Indicators		Power,WPS,WAN, LAN4~1, 5G WIFI,2.4G WIFI
Interfaces		1* 10/100Mbps WAN Port(RJ45) 4* 10/100Mbps LAN Ports(RJ45)
Button		1*Reset/WPS
Antenna		2* fixed omnidirectional antenna and 1* internal antenna
Power Supply		9V/1A adapter
Dimensions (W x D x H)		140 x 100 x 25mm
Environment		Operating Temperature: 0℃~40℃ StorageTemperature:-40℃~70℃ O perating Humidity:10%~90% non-condensing StorageHumidity:5%~95% non-condensing

FULLRIVER Link our dreams